

Shin-Etsu Silicone Primer

PRIMER-AQ-P

PRIMER-AQ-P may be used to increase adhesion to a variety of many common substrates for both glazing and weather sealing application.

It will also contribute to a more uniform and consistent bond and faster adhesion build up.

The drying time of this primer is shorter than conventional primers and so it can contribute to improved productivity.

1 Applications

Glass, Metal, Plastic, Vitreous surface, Coated or painted aluminum

2 Packaging

700 g can

3 General properties

| Parameter | Product name | PRIMER-AQ-P |
|---------------------------|------------------|--------------------------|
| Appearance | | Clear pale yellow liquid |
| Viscosity | | Low |
| Solvent | | n-hexane |
| Drying time at 23°C/50%RH | min | >10 |
| Coverage rate | g/m ² | 50 |

(Not specified values)

4 Instructions for use

PRIMER-AQ-P is designed for improving adhesion to a variety of substrates. To achieve the optimum bonding results, the following steps are recommended:

1. Thoroughly clean the surface with a suitable solvent using the two cloth cleaning method to remove any dirt, oil or grease. Always allow time for the solvent to dry prior to the application of primer.
2. Decant the primer into a small container and apply within 10 minutes, replace the cap on the original container after use and keep it tightly sealed.

3. Apply PRIMER-AQ-P using a clean lint free cloth, if using a brush ensure that only a thin film is applied. Do not over prime, a thin film of primer will provide the best results.
4. Inspect the substrate for signs of a white powder on the surface. If seen this indicates over priming which will negatively affect the adhesion of the sealant. Clean the substrate again with solvent and re-apply the primer.
5. At room temperature and 50%RH, the primer coat should be allowed to dry for 10 minutes.
6. Once primer has been allowed to properly dry, apply RTV silicone sealant as directed.

* Make sure to conduct adhesion tests with actual substrates before using the sealant.

5 Storage conditions

PRIMER-AQ-P should be kept tightly sealed when not in use and stored in temperatures below 27°C.

12 months after production date under the above.

6 Handling precautions

- 1) Seal container tightly and store in a cool, dark place (25°C or below, out of direct sunlight) with good ventilation. Keep away from heat and flame.
- 2) When painting, coating, curing or drying, it is important to keep the product away from heat and flame and provide adequate ventilation.

7 Safety and hygiene

- 1) Organic solvents which contain in PRIMER have skin irritancy. When handling the products, take care to avoid contact with the skin and mucous membranes by using protective glasses and protective gloves. In case of skin contact, immediately wipe off by a dry cloth and then flush thoroughly with running water. In case of accidental eye contact, flush immediately with a large amount of clean water for at least 15 minutes and then seek medical attention. Contact lens wearers must take special care when using the products: if the products enters the eye, the contact lens may become stuck to the eye.
- 2) In the small place, wear a protective mask, and recommend to construct a local exhaust ventilation there. Move to an area with fresh air immediately if you cause dizziness or other unpleasant symptoms by breathing of vapors.
- 3) Keep out of reach of children.
- 4) Be sure to read the Safety Data Sheets (SDS) for these products before use. SDS are available from the Shin-Etsu Sales Department.

CAUTION

- The data and information presented in this catalog may not be relied upon to represent standard values. Shin-Etsu reserves the right to change such data and information, in whole or in part, in this catalog, including product performance standards and specifications without notice.
- Users are solely responsible for making preliminary tests to determine the suitability of products for their intended use. Statements concerning possible or suggested uses made herein may not be relied upon, or be construed, as a guaranty of no patent infringement.
- For detailed information regarding safety, please refer to the Safety Data Sheet (SDS).
- The silicone products described herein have been designed, manufactured and developed solely for general industrial use only; such silicone products are not designed for, intended for use as, or suitable for, medical, surgical or other particular purposes. Users have the sole

responsibility and obligation to determine the suitability of the silicone products described herein for any application, to make preliminary tests, and to confirm the safety of such products for their use.

- Users must never use the silicone products described herein for the purpose of implantation into the human body and/or injection into humans.
- Users are solely responsible for exporting or importing the silicone products described herein, and complying with all applicable laws, regulations, and rules relating to the use of such products. Shin-Etsu recommends checking each pertinent country's laws, regulations, and rules in advance, when exporting or importing, and before using the products.
- Please contact Shin-Etsu before reproducing any part of this catalog. Copyright belongs to Shin-Etsu Chemical Co., Ltd.



<https://www.shinetsusilicone-global.com/>

Shin-Etsu Chemical Co., Ltd.

Marunouchi Eiraku Bldg., 4-1, Marunouchi 1-chome,
Chiyoda-ku, Tokyo 100-0005, Japan

Silicone Division, Sales and Marketing Department IV

Phone : +81-(0)3-6812-2411 Fax : +81-(0)3-6812-2415